



Downlights

For more information on this and other Product Ranges, please contact :
sales@keenlight.com or Visit our web site : www.keenlight.com

Emergency, Sensor and Dimming options available on the following fittings

KL 79



186mm Diameter
102mm Height
176mm Cut Out

Recessed LED Gimbal Downlight
Multi faceted Reflector
Narrow, Medium & Wide beam angles
CRI80 3000K & 4000K
Up to 2803 lumens
White Bezel
Frosted or Blue Highlight or vertical halo
Glass scatter Dome, Clear Glass, Centre Etched
Glass or Fully Etched Glass

KL84



230mm diameter
152mm depth
Suspended versions
Supplied with 2m sus-
pension kit

Surface LED Downlight also available with 2m
suspension kits
Satin etched, Specular or Multi faceted reflectors
CRI80 3000K & 4000K
Up to 2741 lumens
Accessories:
Blue or Frosted Halo
Clear Glass, Centre Etched Glass, Full Etched
glass, Clear or Opal Polycarb
Black, White or Silver

KL87



200mm Diameter
238mm Height
Suspended versions
Supplied with 2m sus-
pension kit

Surface LED Downlight also available with 2m
suspension kits
Satin etched reflector
CRI80 3000K & 4000K
Up to 3625 lumens
Accessories: Blue or Frosted Halo
Clear Glass, Centre Etched Glass, Full Etched
glass, Clear or Opal Polycarb, Prismatic Lens
Black, White or Silver

KL125



244mm x 244mm bezel
82mm Height
220mm x 220mm Out
Out

Recessed square LED Illuminated Light Box
which compliments LED Panels
CRI 80 3000K & 4000K
Up to 1326 lumens
White

KL 130



85mm Diameter
95mm Height
81mm Cut Out

Low Glare Recessed Architectural LED Down-
light
Integral IP44 protective lens and deep matt black
darklight baffle to minimise glare
Softlight baffle an option, along with Plaster-In
kit.
31 & 35 degree Reflectors
CRI80 3000K & 4000K
Up to 874 lumens
White Black or Silver

KL 131



85mm Diameter
05mm Height
31mm Cut out

Low Glare Recessed Architectural LED Wall-
wash
Integral IP44 protective lens and deep matt black
darklight baffle to minimise glare
Softlight baffle an option, along with Plaster-In
kit.
32 & 35 degree Reflectors
CRI80 3000K & 4000K
Up to 749 lumens
White Black or Silver



Downlights

For more information on our range of Downlights and other Product Ranges,
Please contact : sales@keenlight.com or Visit our web site : www.keenlight.com

For Emergency or Dimming versions of all downlights please contact sales office as above

KL 132



85mm x 85mm Outer
95mm Height
81mm x 81mm Cut Out
Double:-
154mm x 85mm Outer
145mm x 77mm Cut Out
Triple:-
222mm x 85mm Outer
213mm x 77mm Cut Out

Rec Square Low Glare Architectural LED Downlight with IP44 protective lens and deepMatt black baffle to minimise glare.
Available as single, double or Triple
32 & 35 degree beam angles
3000K + 4000K
Up to 2623lumens
White, Black or Silver

KL 133



85mm x 85mm Outer
105mm Height
81mm x 81mm Cut Out

Rec. Square Low Glare Architectural LED Wallwash with IP44 protective lens and deep Matt black baffle to minimise glare
Plaster in kit available
32 & 35 degree beam angles
3000K + 4000K
Up to 749 lumens
White, Black or Silver

KL 149



85mm Diameter
60mm Height
73mm Cut Out

Rec Circular LED Downlight IP65
45deg beam angle Multi Facit Reflector
3000K & 4000K
Up to 587 lumens
White, Brushed, or Black

KL 175



76mm Diameter
100mm Height
65mm Cut Out

Rec Mini Pinhole LED Downlight
Wide Range of features including:-
Fixed or tiltable bodies
White gold or black baffle
IP54 Ribbed Glass
Honeycombe Reflector
20 or 40 deg beam angles
2700K 3000K or 4000K
Up to 583 lumens—Tridonic Engine
Black or White Body

KL 176



76mm Diameter
126mm Height
65mm Cut Out

Rec Mini Pinhole LED Downlight
Wide Range of features including:-
Fixed or tiltable bodies
White gold or black baffle
IP54 Ribbed Glass
Honeycombe Reflector
16, 24 or 40 deg beam angles
2700K 3000K or 4000K
Up to 627 lumens - Xicato Engine
Black or White Body



Downlights

For more information on our range of Downlights and other Product Ranges,
Please contact : sales@keenlight.com or Visit our web site : www.keenlight.com

For Emergency or Dimming versions of all downlights please contact sales office as above

KL 2013R/L		190mm Diameter 151mm Height 180mm Cut Out 90 degree scoop 355deg Turn	Rec Circular Adjustable LED Downlight Highly Efficient CRI80 + CRI90 2700K - 5000K 10, 20 24, 30,40 50& 60 deg beam angles UP to 6125 lumens White, Black & Silver
KL 2013R/Lm		164mm Diameter 91mm Height 153mm Cut Out 90 Degree Scoop 355deg Turn	Rec Circular Small & Elegant Adjustable LED Downlight CIR80 + CRI90 2700K—5000K 10, 20 24, 30,40 50& 60 deg beam angles UP to 4475 lumens White, Black & Silver
KL 2013R/M		184mm Diameter 174mm Height 160mm Cut Out	Rec Circular Adjustable LED Downlight Can be used Fixed or Pullout for adjustable display CRI80 + CRI90 15, 24, 36 & 60 beam angles Up to 4560lumens White Black or Silver
KL Celeste		260mm Diameter 72mm Height 235mm Cut Out	Recessed Circular LED Downlight CCT Selectable CRI80 3000K + 4000K Up to 3760 lumens White
KL Eris		12w:- 140mm Diameter 26mm Height 120mm Cut out 22w/27w:- 230mm Diameter 210mm Cut Out	Recessed Circular LED Downlight CCT Selectable CRI80 3000K + 4000K Up to 2625 lumens White
KL Jupiter		230mm x 151mm Overall 95mm depth 215mm x 135mm Cut Out 90 deg scoop	Recessed Rectangular LED Wallwash Dowlight High Output Efficient Luminaire 50d beam angle CRI80 + CRI90 2700K—5000K Various Lumen Output packages White, Silver or Black
KL Taurus		90mm diameter 60mm Hight (7w) 78mm Height (12w) 74mm Cut Out	Reccsed Circular Adjustable LED Downlight CRI80 7w/643lm or 12w/1200lm White



Downlights

For more information on our range of Downlights and other Product Ranges,
Please contact : sales@keenlight.com or Visit our web site : www.keenlight.com

For Emergency or Dimming versions of all downlights please contact sales office as above

KL Trent



180 mm Diameter
122mm Height
170mm Cut Out

Recessed fixed LED
Downlight
CRI80 + CRI90
Up to 6210 lumens
70deg beam angle
2500-K—5000K
Black, White, & Grey

KL Trent M



153mm Diameter
124mm Height
140mm Cut Out

Recessed fixed LED
Downlight
CRI80 + CRI90
Up to 6210 lumens
15,30 & 45 deg beam angle
2500K—5000K
Black, White & Grey

KL Trent A



125mm Diameter
111mm Height
125mm Cut Out

Recessed fixed LED
Downlight
CRI80 + CRI90
Up to 3100 lumens
20 & 50 deg beam angles
2500K—5000K
Black, White & Grey

KL Trent II



180mm Diameter
122mm Height
170mm Cut Out

Recessed fixed LED
Downlight
CRI80 + CRI90
Up to 6210 lumens
70 deg beam angles
2500K—5000K
Black, White & Grey

KL Trent XL



220mm Diameter
218mm Height
170mm Cut Out

Recessed fixed LED
Downlight
CRI80 + CRI90
Up to 8100 lumens
60 deg beam angles
2500K—5000K
Black, White & Grey

KL Trent Z /BW



225mm Diameter
129mm Height
210mm Cut Out

Recessed fixed LED
Downlight
CRI80 + CRI90
Up to 6210 lumens
Bat Wing Distribution
2500K—5000K
Black, White & Grey

KL Trent Z



225mm Diameter
129mm Height
210mm Cut Out

Recessed fixed LED
Downlight
CRI80 + CRI90
Up to 6210 lumens
55deg beam angles
2500K—5000K
Black, White & Grey



Downlights

For more information on our range of Downlights and other Product Ranges, Please contact : sales@keenlight.com or Visit our web site : www.keenlight.com

For Emergency or Dimming versions of all downlights please contact sales office as above

KL Thames V2



27w -280mm Diameter
95mm Height
230mm Cut Out

Recessed Circular LED Downlight
2 sizes—3 outputs
With Opal Acrylic Diffuser
CRI80

15/19w - 244mm Diameter
78mm Height
180mm Cut Out

4000K + 5000K
45deg beam angle
15w/1310lms 19w/ 1750lms 27w/2500lms
White

KLR H11M



80mm Diameter
100mm Depth
74mm Cut Out
90 deg tilt
355deg Turn

Mini Recessed Circular Adjustable LED
Downlight
Beam Angles 18, 28 & 40 Deg
CRI 80 + CRI 90
3000K + 4000K
Up to 11911 lumens
White Silver or Black

KLRA-C93



238mm Diameter
165mm Height
222mm Cut Out

Recessed Circular Asymmetric LED
Downlight
Satin Edged Reflector
CRI80
3000K + 4000K
Up to 2352 lumens
White

Couldn't find what you wanted? Give us a call. 01293 511699 or email sales@keenlight.com,

