



High Bay/Low Bay

For more information on this and other Product Ranges, please contact :
sales@keenlight.com or Visit our web site : www.keenlight.com

KLHB 94



413mm Diameter
420mm Height
2m suspension Kit
(5m kits supplied as extra)

Hi Bay LED Pendant
Polycarbonate Lexalite Reflexr Refractor
Also available with Conical Lens Complete with clamp band
Colour Combinations for gear housing on request
CRI80 3000K & 4000K
Up to 4844 lumens
Touch Dali Dimming available
White, Grey or Black

KLHB 812



313mm Diameter
443mm Height
3m suspension cable
as standard

High Performance Hi Bay LED Pendant
Choice of Acrylic or Aluminium Shade
Gear Housing White, Black or Silver
Beam angles available
15, 20, 30 & 50 deg

CRI80 300K, 4000K, 5000K
CRI90 2700K 3000K 3500K 4000K
Up to 4475 lumens
Dimming Options available

KLHB 816



407mm Diameter
480mm Height
3m suspension cable
as standard

High Performance Hi Bay LED Pendant
Choice of Acrylic or Aluminium Shade
Gear Housing White, Black or Silver
Beam angles available
Mod 1206 - 10, 24 30 & 50deg
Mod 1212 - 20, 40 & 60 deg

CRI80 300K, 4000K, 5000K
CRI90 2700K 3000K 3500K 4000K
Up to 7325 lumens
Dimming Options available

KLHB C218



129mm Diameter
343 Overall Height
Supplied with 3m suspension cable as standard
5m available on request

Versatile High Performance LED Hi Bay Pendant
Beam angles available
Mod 1206 - 10, 24 30 & 50deg
Mod 1212 - 20, 40 & 60 deg

CRI80 3000K, 4000K, 5000K
CRI90 2700K 3000K 3500K 4000K
Up to 7325 lumens

White, Silver or Black

KLHB P1



465mm Diameter
360cm Height
3m Suspension Cable

High Performance LED Hi Bay Pendant
CRI80 & CRI90
2700K—5000K
Up to 3330 lumens

White Silver or Black



High Bay/Low Bay

For more information on this and other Product Ranges, please contact :
sales@keenlight.com or Visit our web site : www.keenlight.com

KLHB AZ20



Size 1
280mm diameter 184mm Height
Size 2
340mm Diameter 187mm Height
Size 3
400mm Diameter 196 Height

High Output IP65 LED Hi Bay Pendant
Die Cast Aluminium Body painted Matt
Black
Toughened Glass front panel with gasket
and painted black steel trim to ensure IP65
3 sizes -
CRI80 4000K 112 degree Beam Angle
Up to 34320 lumens

KLHB H08



Size 1
297mm diameter 246mm Height
Gear housing 152mm diam
Size 2
357mm Diameter 279mm Height
Gear housing 151mm diam
Size 3
357mm Diameter 279 Height
Gear Housing 192mm diam

High Output IP65 LED Hi Bay Pendant
Die Cast Aluminium Body with suspension
hook
Optional Reflector and PC cover
3 sizes
CRI80 5000K 110 degree Beam Angle
Up to 31000 lumens
Dimming Available

KLLB K11



590mm x 320mm
97mm depth

Easy to install LED Low Bay
Surface Mount
Clear Polycarbonate UV Stable Filter
CRI80 4000K
16500lm
White

KLLB M1300



617mm x 465mm
113mm depth

Easy to install LED Low Bay
Surface Mount
Steel body - PC Cover and Wire Guard
optional extras
CRI80 4000K
12000lm & 16000lm
White
Emergency, Dimming and Sensor options
available

KLLB SB31



610mm x 310mm x 200mm
OR
603mm x 131mm x 158mm

Shoe Box LED Low Bay
Replaces 250w & 400w Metal Halide Units
2 sizes
10000lumens or 13500 lumens
CRI 80 5000K as standard—others availa-
ble on request
Options available:-
Emergency,
PIR/ Daylight Dimming Sensors
IP65 Rated Casings
Non Dimming

White