



# Track Lights -Target Range

For more information on this and other Product Ranges, please contact :  
 sales@keenlight.com or Visit our web site : www.keenlight.com

All Track fittings for use with Global 3 circuit track adaptor as standard. Single track adaptor available on request



KL Target A



Head :-  
 106mm Diameter  
 112mm depth  
 Gear Housing:  
 140mm Height

Track mounted LED Track Light

CRI 80 & CRI90  
 2400K.– 5000K  
 Beam Angles 15, 20, 30 45 & 60 degree

Overall width (head and housing) 163mm

858—3867 lumens available dependant on CCT and CRI

White, Black & Silver

KL Target D  
 ( also available with Barn Doors—Option DK)



110mm Diameter  
 240mm length

Track mounted LED Track Light

CRI 80 & CRI90  
 2400K.– 5000K  
 Beam Angles 15, 20, 30 45 & 60 degree  
 858—3330 lumens available dependant on CCT and CRI

Barn doors  
 92mm depth  
 145mm width

Mini Version available  
 200mm length  
 70mm diameter

Mini version 858 - 2576 lumens

White, Black & Silver

KL Target F



Head  
 104mm length  
 115mm diameter  
 Housing  
 244mm length  
 48mm depth

Track mounted LED Track Light

CRI 80 & CRI90  
 2400K.– 5000K  
 Beam Angles 15, 20, 30 45 & 60 degree  
 858—3330 lumens available dependant on CCT and CRI

White, Black & Silver

KL Target N



Head  
 170mm length  
 95mm diameter  
 Housing  
 170mm length  
 42mm depth

Track mounted LED Track Light

CRI 80 & CRI90  
 2400K.– 5000K  
 Beam Angles 15, 30 & 45 degree  
 858—3330 lumens available dependant on CCT and CRI

White, Black & Silver



# Track Lights - Slimline Driver

For more information on this and other Product Ranges, please contact :  
sales@keenlight.com or Visit our web site : [www.keenlight.com](http://www.keenlight.com)

All Track fittings for use with Global 3 circuit track adaptor as standard. Single track adaptor available on request



KL-2013T/016C



Head  
83mm long  
75mm diameter  
Driver  
228mm long  
32mm width

Track Mounted LED Fitting  
80 degree Tilt adjustment  
CRI80 -& CRI 90  
2700K - 5000K  
Beam Angles—15,21,32 & 46 degree  
Up to 3150 lumens  
White, Black or Silver

KL-2013T/016Caf



Head  
108mm long  
100mm diameter  
Driver  
228mm long  
32mm width

Track Mounted LED Fitting  
80 degree Tilt adjustment  
CRI80 -& CRI 90  
2700K - 5000K  
Beam Angles—15,20 30 & 50 degree  
Up to 3675 lumens  
White, Black or Silver

KL-2013T/016R



Head  
108mm long  
100mm diameter  
Driver  
228mm long  
32mm width

Track Mounted LED Fitting  
75 degree Tilt adjustment  
CRI80 -& CRI 90  
2700K - 5000K  
Beam Angles—10,20 24, 30/40 & 50/60 degree  
Up to 4075 lumens  
White, Black or Silver

KL-2013T/016S



Head  
92mm long  
84mm diameter  
Driver  
228mm long  
32mm width

Track Mounted LED Fitting  
85 degree Tilt adjustment  
CRI80 -& CRI 90  
2700K - 5000K  
Beam Angles—15,20 30 & 50 degree  
Up to 3575 lumens  
White, Black or Silver



# Track Lights - High Performance

For more information on this and other Product Ranges, please contact :  
 sales@keenlight.com or Visit our web site : www.keenlight.com

All Track fittings for use with Global 3 circuit track adaptor as standard. Single track adaptor available on request



KL-2013T/AL



Head  
 108mm long  
 100mm diameter  
 Driver  
 124mm long  
 147mm width

Track Mounted LED Fitting  
 90 degree Tilt adjustment  
 CRI80 -& CRI 90  
 2700K - 5000K  
 Beam Angles—15,20,30 & 50 degree  
 Up to 5050 lumens  
 White, Black or Silver

KL-2013T/GS



Head  
 83mm Diameter  
 108mm Long  
 Driver  
 122mm long  
 35mm width

Track Mounted LED Fitting  
 85 degree Tilt adjustment  
 CRI80 -& CRI 90  
 2700K - 5000K  
 Beam Angles—15,20,30 & 50 degree  
 Up to 4475 lumens  
 White, Black or Silver

KL-2013T/GM



Head  
 100 mm diameter  
 From head to driver—  
 154mm

Track Mounted LED Fitting  
 85 degree Tilt adjustment  
 CRI80 -& CRI 90  
 2700K - 5000K  
 Beam Angles—15,20,30 & 50 degree  
 Up to 4475 lumens  
 White, Black or Silver

KL-2013T/GT



Head  
 129 mm diameter  
 From head to driver—  
 187mm

Track Mounted LED Fitting  
 90 degree Tilt adjustment  
 CRI80 -& CRI 90  
 2700K - 5000K  
 Beam Angles—10/20 24, ,30/40 50/60 degree  
 Up to 7325 lumens  
 White, Black or Silver

KL-2013T/TMC



Head  
 79mm long  
 75mm diameter  
 Driver  
 194mm long  
 44mm width

Track Mounted LED Fitting  
 80 degree Tilt adjustment  
 CRI80 -& CRI 90  
 2700K - 5000K  
 Beam Angles—15, 21, ,32 46 degree  
 Up to 3800 lumens  
 White, Black or Silver



# Track Lights - High Performance

For more information on this and other Product Ranges, please contact :  
sales@keenlight.com or Visit our web site : www.keenlight.com

All Track fittings for use with Global 3 circuit track adaptor as standard. Single track adaptor available on request



KL-2013T/H



Head  
108mm long  
100mm diameter  
Driver  
125mm long  
42mm width

Track Mounted LED Fitting  
85 degree Tilt adjustment  
CRI80 -& CRI 90  
2700K - 5000K  
Beam Angles—15,20,30 & 50 degree  
Up to 5125 lumens  
White, Black or Silver

KL-2013T/TL



Head  
129mm Diameter  
Head to top of driver  
188mm  
Driver  
194mm long  
86mm width

Track Mounted LED Fitting  
80degree Tilt adjustment  
CRI80 -& CRI 90  
2700K - 5000K  
Beam Angles—10,20,24,30, 40, 50 & 60degree  
Up to 7325 lumens  
White, Black or Silver

KL-2013T/LM



Head  
100mm diameter  
Driver  
158mm long  
65mm width

Track Mounted LED Fitting  
90 degree Tilt adjustment  
CRI80 -& CRI 90  
2700K - 5000K  
Beam Angles—15,20,30 & 50 degree  
Up to 4475 lumens  
White, Black or Silver



# Track Lights - Linear

For more information on this and other Product Ranges, please contact :  
sales@keenlight.com or Visit our web site : [www.keenlight.com](http://www.keenlight.com)

All Track fittings for use with Global 3 circuit track adaptor as standard. Single track adaptor available on request



KL-2018T/N800  
KL-2018T/N1200  
KL-2018T/N2400



Length 812mm/  
1212mm/2412mm  
Width 82mm  
Height 52mm

Versatile Track Mounted Luminaire  
Asymmetric, Micro prismatic Lens or Opal Diffusers  
Mounting Options  
Adaptor Tilt or fixed  
Suspended, Rail Bracket, Telescopic arm—  
also 45 degree arm, ceiling bracket  
CRI80 or CRI80 +  
3000K + 4000K  
6875—21450 lumens  
White Silver or Black

KL - 2018T/Rsp  
Single or Twin



Length  
463mm /469mm  
Width 32mm /  
56mm  
Depth 43mm

Track Mounted Luminaire  
Asymmetric, Direct or Opal Diffusers  
CRI80 +  
3000K + 4000K  
Single 1770lm / 1800lm  
Twin 3540lm / 3600lm  
White